



Swiss precision for excellent audio quality

VOICE TECHNOLOGIES



VT760MKII Omni Headset Combination

Highest flexibility for your best performance.

The Voice Technologies VT760MKII is designed to fit any head contour and to free performers to focus on their performance! Ideal for TV, 2-way radio applications, public speaking and broadcast studio operations.





The VT760MKII has an extended frequency response and an omnidirectional polar pattern for outstanding clarity and natural sound. The flexible gooseneck enables the user to position the microphone for optimum sound and gain before feedback.

It is very comfortable and unobtrusive. A one size fits all soft earpiece is connected to the integrated earphone VT600. The microphone capsule and boom are moisture protected by molded injection.

Colors: beige

Application area: [Broadcast studio operations - Presentations](#)

The VT760MKII comes in an elegant black case with the following accessories:

	STRAP	Colors: beige or black
	EAR/BEIGE	
	FLEXIBLE EAR INSERT (OPTIONAL)	for left or right ear (S/M/L or XL)
	Case4	Size: 190x210x100mm

Audio Bauer Pro AG, Bernerstrasse-Nord 182, CH-8064 Zürich, Switzerland
Phone: +41 44 432 32 30, Email: info@vt-switzerland.com

www.vt-switzerland.com

Specifications	
Generating Element:	Electret Condenser
Polar pattern:	Omni-Directional
Frequency Range:	100Hz- 18kHz
Sensitivity (@1kHz):	-43dB ±3dB 1V/microbar (7.1mV/Pa)
Noise Level	32dB "A" weighted
Max. Input SPL:	125dB
Impedance:	2.8 to 6.8 kOhms, nominal 4.4 kOhms
Bias/+VDC:	1.5V to 9.0V (max.)
Dynamic Range:	93dB
Signal Noise Ratio:	62dB @94dB SPL
Color:	beige
Cable:	Length 1,5m Ø 2mm
Weight;	42 g
<u>Earphone:</u>	
Element:	Subminiature Magnetic Receiver
Frequency Response:	200Hz-8kHz
Impedance:	500 kOhm
Sensitivity:	104+/-3dB
Distortion:	5% max.
Color:	beige

Wiring Configuration (3-wire):	
Red	+VDC
Copper	Ground
Blue (Transparent)	NF

